

JS Mechanic



• Air Impact Wrench



ST-65883 W1" Anvil
ST-65883-B W1/8" Anvil
1" Heavy Duty Impact Wrench (Twin Hammer)
Torque: 2,500 ft-lb



ST-6660
3/4" Heavy Duty Impact Wrench (Twin Hammer)
Torque: 1,100 ft-lb



ST-6669
3/4" Heavy Duty Impact Wrench (Twin Hammer)
Torque: 1,200 ft-lb



ST-C562 W1" Anvil
ST-C562-2 W2" Anvil
ST-C562-6 W1/8" Anvil
3/4" Heavy Duty Impact Wrench (Twin Hammer)
Torque: 1,000 ft-lb

• Air Ratchet Wrench



ST-55550AT 3/8" (Two Pawl)
ST-55550T 1/4" (Two Pawl)
ST-55550A 3/8" (Single Pawl)
ST-55550 1/4" (Single Pawl)
Air Ratchet Wrench
Torque: 30 ft-lb



• Air Drill



ST-4438
3/8" Reversible Angle Drill
Speed: 1,800 rpm



ST-4438
3/8" Air Straight Drill
Speed: 2,600 rpm



ST-4434A
3/8" Heavy Duty Reversible Air Drill
Speed: 1,800 rpm

• Air Screwdriver Auto Shut Off

Push Start

Full-auto shut off air composite screwdriver



• Spring Balancer



SA-2201 (0.3-0.8kg)
SA-2203 (0.6-1.5kg)
SA-2203-1 (1.0-2.0kg)
SA-2204 (1.5-3.0kg)
SA-2207 (3.0-5.0kg)
Spring Balancer



SA-22015T (0.5-1.5kg)
SA-22030T (1.5-3.0kg)
SA-22050T (3.0-5.0kg)
Air PU Hose Balancer
(PU Hose Dia: 6.5X10mm)



HR-0130 (5.5X3.5 mmØBM)
HR-0180 (5X8mmØ7.5M)
Air PU Hose Balancer

SA-22015 (0.5-1.5kg)
Spring Balancer

Model No.	Free Speed (r.p.m.)	Torque Range (Kg-cm)	Weight (g)	O.A.L. (mm)	Dia (mm)	Noise Level (+2dBA)	Min. air hose bore		Air Consumption (m ³ /min)	Standard Deviation (%)	Fastening Capacity	
							6kg/cm ³	5kg/cm ³			Machine Screw Dia.	Tapping Screw Dia.
											T	2T
CP10	1000	0.5-2	480	180	31	70	5.0	6.35	0.20	+3	M1.0-M2.2	M1.1-M1.7
CP20	1000	1-8	480	180	31	70	5.0	6.35	0.20	+3	M1.7-M3.3	M1.3-M2.7
CP30	1800	3-17	480	180	31	74	5.0	6.35	0.28	+3	M2.2-M4.2	M1.7-M3.2
CP35	2200	3-20	480	180	31	74	5.0	6.35	0.28	+3	M2.2-M4.5	M2.0-M3.5
CP38	1800	3-25	480	180	31	74	5.0	6.35	0.28	+3	M2.2-M4.7	M1.7-M3.8
CP40	1000	5-30	480	180	31	74	5.0	6.35	0.28	+3	M2.8-M5.0	M2.2-M4.0
CP45	800	8-40	480	180	31	78	5.0	6.35	0.30	+3	M3.3-M5.7	M2.7-M4.4
CP48	1700	5-45	790	215	39	78	8.0	9.5	0.55	+3	M2.8-M5.8	M2.2-M4.7
CP50	1400	7-50	790	215	39	78	8.0	9.5	0.55	+3	M2.9-M6.0	M2.8-M4.9
CP55	1000	7-65	790	215	39	78	8.0	9.5	0.55	+3	M2.9-M6.4	M2.8-M5.4
CP60	550	15-95	790	215	39	78	8.0	9.5	0.55	+3	M4.1-M7.0	M3.1-M6.0
CP65	300	30-180	810	215	39	78	8.0	9.5	0.55	+3	M5.0-M9.3	M4.0-M7.2
CP68	250	50-280	810	215	39	78	8.0	9.5	0.55	+3	M6.0-M11.0	M4.9-M8.7

• Air Angle Die Grinder



ST-77364G
4" Mini Angle Grinder (Roll Type) W/O disc
Speed: 13,000 rpm



ST-77364
4" Mini Angle Grinder (Lever Type) W/O disc
Speed: 13,000 rpm



ST-7830G 2"
Air Angle Grinder



ST-7844G 4"
ST-7844G 5"
Air Angle Grinder

(Lever Type) 1HP



ST-7871G-A 7" spindle: 5/8"X11UNF
ST-7871G-B 7" spindle: 1/2"X16
Air Angle Grinder (Rotary Type) 1.3 HP

SUMAKE

• Air Die Grinder



ST-7432 1/4"
ST-7432M 6mm
Air Die Grinder



ST-7432G 1/4"
ST-7432GM 6mm
Air Die Grinder



ST-7732 1/4"
ST-7732M 6mm
Mini Air Die Grinder
Speed: 25,000 rpm



ST-7733 1/4"
ST-7733M 6mm
Air Die Grinder
Speed: 22,000 rpm



ST-7734 1/4"
ST-7734M 6mm
Air Angle Die Grinder
Speed: 20,000 rpm

• Air Nib Sander



ST-77471
Front exhaust With 1-1/4" Velcro Pad
(option: Sticker Pad No. ST-77471S)
Free speed 7,500 rpm
(option: 5,000 rpm / 10,000 rpm)

• Air Orbital Sander (Double Action)



ST-7108NC(S)-5 ST-7108DC(S)-6
ST-7108NC(S)-6 ST-7108VC(S)-5
ST-7108DC(S)-5 ST-7108VC(S)-6
(10,000 rpm)



ST-7112NC(S) (10,000 rpm)
Non-Vacuum Jitterbug Sander
W/Velcro (Stick) Pad
(110X100 mm)



ST-7729 NC(S)

• Air Sander



ST-7147
Air Diamond Sander
W/2" Pad



ST-7148
Air High Speed Sander/
Grinder W/3" Pad



ST-7149
Air Polisher/Sander
W/3" Pad Base



ST-7150
Air Finger Sander
W/4" Pad



7150-38
7150-38A (option)
7150-39
7150-39A
7150-40

• Sanding Pad

P-20NC(S)1, P-20NC(S)2	P-A20NC(S)	P-A30NC(S)
2" Pad	2" Pad	3" Pad
Pin Spindle P-20NC(S)1 W/ØMØ20mm (L) P-20NC(S)2W/Ø1/4"X13/16" (L)	5/16" 24UNF	5/16" 24UNF

P-G50NC, P-G50NS	P-G55VC, P-G55VS	P-G56VC, P-G56VS
5" Pad	5" Pad	5" Pad

• Air Belt Sander



ST-7709
Air Belt Sander (10X330mm)
Speed: 16,000 rpm
Grinding Belt
7709-01A #80
7709-01B #100
7709-01C #120



ST-7710
Air Belt Sander (20X520mm)
Speed: 16,000 rpm
Grinding Belt
7710-07A #80
7710-07 #100

• Air Rivet



ST-66159 3/16" (4.8mm)
Air Hydraulic Riveter

• Air Spray Gun



SS-77G
Gravity Air Spray Gun

• Air Blow Gun



SA-5515
SA-5515B W/Brass Thread
(100mm-Tube)

• Mini Die Grinder



ST-10G 3mm
ST-10GS 1/8"
Air Industrial Grinder
(Roll Type)



ST-3372 1/8"
ST-3372M 3mm
Air Micro Die Grinder
(90,000 rpm)



ST-3391
90° Air Micro Grinder
(21,000 rpm)



ST-3392
120° Air Micro Grinder
(21,000 rpm)



SA-3330 3/8"
SA-3340 1/4"
Mini Oiler

COUPLER Normal

ITEM	SIZE	MATERIAL
	20SM 1/4" male	Steel
	30SM 3/8" male	Steel
	40SM 1/2" male	Steel
	20SF 1/4" female	Steel
	30SF 3/8" female	Steel
	40SF 1/2" female	Steel
	20SH 1/4"	Steel
	25SH 5/16"	Steel
	30SH 3/8"	Steel
	40SH 1/2"	Steel
	20SP 5 mm x 8 mm	Steel
	30SP 6.5 mm x 10 mm	Steel
	40SP 8 mm x 12 mm	Steel
	45SP 8.5 mm x 12.5 mm	Steel

COUPLER One Touch

ITEM	SIZE	MATERIAL
	20SMO 1/4" male	Steel
	30SMO 3/8" male	Steel
	40SMO 1/2" male	Steel
	20SFO 1/4" female	Steel
	30SFO 3/8" female	Steel
	40SFO 1/2" female	Steel
	20SHO 1/4"	Steel
	25SHO 5/16"	Steel
	30SHO 3/8"	Steel
	40SHO 1/2"	Steel
	20SPO 5 mm x 8 mm	Steel
	30SPO 6.5 mm x 10 mm	Steel
	40SPO 8 mm x 12 mm	Steel
	45SPO 8.5 mm x 12.5 mm	Steel

PLUG Normal

ITEM	SIZE	MATERIAL
	20PM 1/4" male	Steel
	30PM 3/8" male	Steel
	40PM 1/2" male	Steel
	20PH 1/4"	Steel
	25PH 5/16"	Steel
	30PH 3/8"	Steel
	40PH 1/2"	Steel
	20PPS 5 mm x 8 mm	Steel
	30PPS 6.5 mm x 10 mm	Steel
	40PPS 8 mm x 12 mm	Steel
	45PPS 8.5 mm x 12.5 mm	Steel

ITEM	SIZE (PU Tube)	MATERIAL
20SPG (SPGS)	5 mm x 8 mm	STEEL PLUG + POLY GUARD
30SPG (SPGS)	6.5 mm x 10 mm	STEEL PLUG + POLY GUARD
40SPG (SPGS)	8 mm x 12 mm	STEEL PLUG + POLY GUARD
42SPG (SPGS)	8.5 mm x 12.5 mm	STEEL PLUG + POLY GUARD

ITEM	SIZE (PU Tube)	MATERIAL
20PPG (PPGS)	5 mm x 8 mm	STEEL PLUG + POLY GUARD
30PPG (PPGS)	6.5 mm x 10 mm	STEEL PLUG + POLY GUARD
40PPG (PPGS)	8 mm x 12 mm	STEEL PLUG + POLY GUARD
42PPG (PPGS)	8.5 mm x 12.5 mm	STEEL PLUG + POLY GUARD

COUPLER One Touch, Lockable, Swivel

ITEM	SIZE (PU Tube)	MATERIAL
NSC20SP	5 mm x 8 mm	Steel
NSC30SP	6.5 mm x 10 mm	Steel
NSC40SP	8 mm x 12 mm	Steel
NSC45SP	8.5 mm x 12.5 mm	Steel

COUPLER Large Flow

ITEM	SIZE	MATERIAL
	400SM 1/2" male	Steel
	600SM 3/4" male	Steel
	800SM 1" male	Steel
	400SF 1/2" female	Steel
	600SF 3/4" female	Steel
	800SF 1" female	Steel
	400SM 1/2" (13mm)	Steel
	600SM 3/4" (19mm)	Steel
	800SM 1" (25mm)	Steel

PLUG Big Flow

ITEM	SIZE	MATERIAL
	400PM 1/2" male	Steel
	600PM 3/4" male	Steel
	800PM 1" male	Steel
	400PF 1/2" female	Steel
	600PF 3/4" female	Steel
	800PF 1" female	Steel
	400PH 1/2"	Steel
	600PH 3/4"	Steel
	800PH 1"	Steel